



CEMENT & BOOM HOSE

Our selection of cement and boom hoses are designed and built to assure maximum life and the best performance while on the job. Hydraulic Supply Company stocks the most common sizes and lengths of pre-assembled hoses complete with heavy duty couplings. Additional hose and couplings are also in stock, ready to be assembled to customer required lengths.

EHK007 MAURAUER™ Heavy Duty Wire Reinforcement



Application: High-pressure concrete pumping
Tube: Abrasion resistant synthetic rubber
Reinforcement: High-tensile steel cords
Cover: Pin-pricked synthetic rubber
Temp: -40°C to +70°C, (-40°F to +158°F)
Pressure: 85 bar / 1230 psi
Burst: 2900 psi
Size Range: 2" - 5"

EHK006 MAURAUER™ Heavy Duty Textile Reinforcement



Application: High-pressure concrete pumping, spraying plaster, grout, sand, gypsum, and ready-mixed concrete
Tube: Abrasion resistant synthetic rubber
Reinforcement: High-tensile synthetic textile and anti-static copper wire
Cover: Pin-pricked synthetic rubber
Temp: -40°C to +70°C, (-40°F to +158°F)
Pressure: 85 bar / 1230 psi
Burst: 2580 psi
Size Range: 2" - 5"

EHK029 Plaster & Grout Textile Reinforcement



Application: High-pressure concrete pumping, spraying plaster, grout, sand, gypsum, and ready-mixed concrete
Tube: Abrasion resistant synthetic rubber
Reinforcement: High-tensile synthetic textile and anti-static copper wire
Cover: Pin-pricked synthetic rubber
Temp: -40°C to +70°C, (-40°F to +158°F)
Pressure: 69 bar / 1000 psi
Burst: 2030 psi
Size Range: 2" - 2 1/2 - 3"

Metric and Victaulic couplings are available for special order.



Call us today! Ph.844-966-2535 | www.hydraulic-supply.com



EHK007 MAURAUDE™ Heavy Duty Wire Reinforcement

Part No.		Hose I.D.			Hose O.D.		Max Operating Pressure		Burst Pressure		r Minimum Bend Radius		Weight		Length		
	mtr	ft	DN	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	mtr	ft
EHK007-32-	MXX	100	51	50,8	2.00	70,0	2.76	85	1230	200	2900	275	10.83	3,03	2.04	40-61	100
EHK007-40-	MXX	100	60	63,5	2.50	88,0	3.46	85	1230	200	2900	300	11.81	4,48	3.01	40-61	100
EHK007-48-	MXX	100	80	76,2	3.00	102,0	4.02	85	1230	200	2900	350	13.78	5,46	3.67	40-61	100
EHK007-64-	MXX	100	102	101,6	4.00	130,0	5.12	85	1230	200	2900	400	15.75	8,46	5.69	40-61	100
EHK007-80-	MXX	100	130	127,0	5.00	155,0	6.10	85	1230	200	2900	500	19.69	9,63	6.47	40-61	100

EHK006 MAURAUDE™ Heavy Duty Textile Reinforcement

Part No.		Hose I.D.			Hose O.D.		Max Operating Pressure		Burst Pressure		Weight		Length		
	mtr	ft	DN	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHK006-32-	MXX	100	51	50,8	2.00	70,0	2.76	85	1230	178	2580	2,13	1.43	40-61	100
EHK006-40-	MXX	100	60	63,5	2.50	84,0	3.31	85	1230	178	2580	2,58	1.73	40-61	100
EHK006-48-	MXX	100	80	76,2	3.00	102,0	4.02	85	1230	178	2580	4,05	2.72	40-61	100
EHK006-64-	MXX	100	102	101,6	4.00	130,0	5.12	85	1230	178	2580	5,90	3.96	40-61	100
EHK006-80-	MXX	100	130	127,0	5.00	155,0	6.10	85	1230	178	2580	6,93	4.66	40-61	100

EHK029 Plaster & Grout Textile Reinforcement

Part No.		Hose I.D.		Hose O.D.		Max Operating Pressure		Burst Pressure		Weight		Length		
	mtr	ft	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHK029-24-	MXX	100	38	1.50	56	2.20	69	1000	140	2030	1,60	3.53	40-61	100
EHK029-32-	MXX	100	51	2.00	70	2.75	69	1000	140	2030	2,02	4.45	40-61	100
EHK029-40-	MXX	100	63	2.48	84	3.30	69	1000	140	2030	2,79	6.15	40-61	100
EHK029-48-	MXX	100	76	2.99	102	2.99	69	1000	140	2030	4,16	9.17	40-61	100